

## MEF EMC-FILTER 1-PHASE 2-STAGE

I:16A U:250 VAC/300 VDC snap on

Art.No.: 10466

Weight: 0.317

Country of origin: IT

Model designation: MEF 1/2 SY 16A T

Current: 16 A

DIN-rail mountable



Attenuation curves on request.

against symmetrical interferences

The single phase 2-stage EMC filters MEF 1/2 are used in the range 0.1...30 MHz to suppress cable carried interference on mains and control cables. The best filter performance is achieved by using short connection wires (suggestion: earth connection < 10 cm) and the largest possible diameter. The EMC filters work bi-directionally (in both directions). The filters are for demanding applications. The filters are designed for use with fixed modules. One step of the filter is always for the suppression of asymmetrical interferences (magnetically compensated suppression). The second step is, dependant on application for symmetrical or asymmetrical interferences.

### [Link to Product](#)

#### Illustration



Product may differ from Image

**General product information**

|                                |   |
|--------------------------------|---|
| Suitable for application range | Devices with high repetition rates of switching operations, Phase angle control, Power Supply Units, after transformers, supply of universal motors |
| Suitable for type of fault     | symmetrical interferences   |

**Commercial data**

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27130806      |
| ECLASS-6.1            | 27420201      |
| ECLASS-7.0            | 27420290      |
| ECLASS-8.0            | 27420290      |
| ECLASS-9.0            | 27420290      |
| ECLASS-10.1           | 27420208      |
| ECLASS-11.1           | 27420208      |
| ECLASS-12.0           | 27420208      |
| ETIM-5.0              | EC002498      |
| customs tariff number | 85363010      |
| customs tariff number | 85363010      |
| GTIN                  | 4048879029339 |
| GTIN                  | 4048879029339 |
| Packaging unit        | 1             |
| Packaging unit        | 1             |

**Electrical data**

|                      |                        |
|----------------------|------------------------|
| Leakage current max. | 5 mA @ 250 V AC, 50 Hz |
|----------------------|------------------------|

**Electrical data | Supply**

|                           |              |
|---------------------------|--------------|
| Power frequency           | 50 ... 60 Hz |
| Operating voltage AC max. | 250 V        |
| Operating voltage DC max. | 300 V        |

**Electrical data | Output**

|                  |   |
|------------------|---|
| Overload current | 18× (IN t) max. 0.5 ms; 1.5× (IN t) max. 1 min. (1× per hour) |
|------------------|---|

**Installation**

|  |                     |
|--|---------------------|
| Connection cross-section solid min.                  | 0,2 mm <sup>2</sup> |
| Connection cross-section solid max.                  | 6 mm <sup>2</sup>   |
| Connection cross-section stranded/fine-stranded min. | 0,2 mm <sup>2</sup> |
| Connection cross-section stranded/fine-stranded max. | 4 mm <sup>2</sup>   |
| AWG number solid min.                                | 24                  |
| AWG number solid max.                                | 9                   |
| AWG number stranded/fine stranded min.               | 24                  |
| AWG number stranded/fine stranded max.               | 11                  |

**Device protection | Electrical**

|                                  |        |
|----------------------------------|--------|
| Duration insulation test voltage | 2 s    |
| Insulation test voltage L-L      | 2,1 kV |
| Insulation test voltage L-N      | 2,7 kV |

**Mechanical data | Mounting data**

|                            |                                |
|----------------------------|--------------------------------|
| Mounting method            | geschnappt                     |
| Suitable for mounting type | Mounting rail TH35, (EN 60715) |
| Height                     | 107 mm                         |

|       |       |
|-------|-------|
| Width | 56 mm |
| Depth | 39 mm |

#### Environmental characteristics | Climatic

|                                    |           |
|------------------------------------|-----------|
| Climatic category (EN IEC 60068-1) | 25/085/21 |
|------------------------------------|-----------|

#### Connection type 3

|            |                    |
|------------|--------------------|
| Connection | Screw terminals SK |
|------------|--------------------|

|                          |          |
|--------------------------|----------|
| Family construction form | terminal |
|--------------------------|----------|

|        |        |
|--------|--------|
| Gender | female |
|--------|--------|

|                       |              |
|-----------------------|--------------|
| Color contact carrier | green-yellow |
|-----------------------|--------------|

|              |   |
|--------------|---|
| No. of poles | 1 |
|--------------|---|

|       |    |
|-------|----|
| PIN 1 | PE |
|-------|----|

|            |                    |
|------------|--------------------|
| Connection | Screw terminals SK |
|------------|--------------------|

|                          |          |
|--------------------------|----------|
| Family construction form | terminal |
|--------------------------|----------|

|                       |      |
|-----------------------|------|
| Color contact carrier | gray |
|-----------------------|------|

|              |   |
|--------------|---|
| No. of poles | 2 |
|--------------|---|

|       |   |
|-------|---|
| PIN 1 | L |
|-------|---|

|       |   |
|-------|---|
| PIN 2 | N |
|-------|---|

|            |                    |
|------------|--------------------|
| Connection | Screw terminals SK |
|------------|--------------------|

|                          |          |
|--------------------------|----------|
| Family construction form | terminal |
|--------------------------|----------|

|                       |      |
|-----------------------|------|
| Color contact carrier | gray |
|-----------------------|------|

|              |   |
|--------------|---|
| No. of poles | 2 |
|--------------|---|

|       |    |
|-------|----|
| PIN 1 | L' |
|-------|----|

|       |    |
|-------|----|
| PIN 2 | N' |
|-------|----|