


Modlight Illumix Xtreme Line 27W

LED machine lamp, IP69K, 24VDC, M12 connection

Link to Product Illustration ○ ENERG[†] Murrelektronik GmbH Light source Modlight Illumix XL/25015 А F 21 kWh/1000h PIMURR

Product may differ from Image



Commercial data	
ECLASS-6.0	27110303
ECLASS-6.1	27110390
ECLASS-7.0	27110390
ECLASS-8.0	27110390
ECLASS-9.0	27110345
ECLASS-10.1	27110345
ECLASS-11.1	27110345
ECLASS-12.0	27110345
ETIM-5.0	EC001334
customs tariff number	94054239
GTIN	4048879439169
Packaging unit	1
Electrical data Supply	
Operating voltage DC	24 V
Current consumption max.	1120 mA
HMI Illumination properties	
Illumination level	860 lx
Installation Connection	
Family construction form	M12
Installation Pin assignment	
No. of poles	5
Device protection Electrical	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-28

Murrelektronik GmbH | Falkenstraße 3 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com



Degree of protection (ISO 20653:2013)	IP69K	
Additional condition protection degree	inserted, screwed	
Mechanical data Material data		
Housing properties	with stainless steel cover	
Material housing	Aluminium	
Mechanical data Mounting data		
Height	43 mm	
Width	97 mm	
Depth	441 mm	
Environmental characteristics Climatic		
Operating temperature min.	-20 °C	
Operating temperature max.	55 °C	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-28

Murrelektronik GmbH | Falkenstraße 3 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com