

M12 FEMALE 0°



PVC 3X0.34 GRAY, UL/CSA 6m

Female



M12, 3

Art-No. 7005 -M12 Lite (,) .

stay connected



Female



* UL/CSA

cCSAus

12181

/ 3 x 0.34 mm²

PVC (, ,)

	PVC (UL/CSA)
	4.6 mm ±5%
()	10× Ø
()	-30...+80 °C
()	-5...+80 °C
	213
	1 (PVC)
()	UL (AWM-Style 2464/1731), CSA
[G/m]	34,10
(wire)	,
()	max. 60 Ω/km (20 °C)
-Ø	0.15 mm
()	19× 0.15 mm (5)
()	3× 0.34 mm ²
AWG	AWG 22
()	PVC
()	CFC, , ,
()	45 ±5 D
-Ø	1.25 mm ±5%
/	, ,
	3
(shielded)	no
	PVC
()	CFC, , ,
()	85 ±5 A
-Ø ()	4.6 mm ±5%
()	, ,
	UL 300 V AC
	2000 V AC
	DIN VDE 0298-4
()	-30...+80 °C
()	-5...+80 °C
()	5× Ø
()	10× Ø
	max. 250 V AC/DC
(UL)	max. 30 V AC/DC
	max. 4 A
	2.5 kV
	IEC 60664-1, category I
	3
	A-coded
	(M12×1 mm) 0.6 Nm ,
	M12 (SW13)
	IP65, IP66K, IP67 (EN 60529)
Locking	,
	PUR
(-Ø)	10 mm

	DIN EN 61076-2-101 (M12)
	3
()	20 mm
	-25...+85 °C ()
EAN	4048879366267
eClass	27279218
	85444290
	DE
	1